

Package: DepLogo (via r-universe)

October 6, 2026

Type Package

Title Dependency Logo

Version 1.2.2

Maintainer Jan Grau <grau@informatik.uni-halle.de>

Description Plots dependency logos from a set of aligned input sequences.

License GPL-3

NeedsCompilation no

RoxygenNote 7.3.1

Encoding UTF-8

VignetteBuilder knitr

Suggests knitr, rmarkdown, testthat

Author Jan Grau [aut, cre], Jens Keilwagen [aut], Martin Nettling [aut]

Repository <https://jgraux.r-universe.dev>

Date/Publication 2025-10-09 22:10:02 UTC

RemoteUrl <https://github.com/cran/DepLogo>

RemoteRef HEAD

RemoteSha 5d8952ce4547aa9b715fad06ded4d23e84937014

Contents

Alphabet	2
alphabet.dna	3
alphabet.dna.gap	3
alphabet.protein	3
alphabet.protein.gap	4
alphabet.rna	4
alphabet.rna.gap	4
colorchart	5

deprects	6
DLData	7
filter.by.conservation	8
filter.by.dependencies	9
filter.by.gaps	10
filterColumns	10
getDeps	11
getPWM	12
logo	13
partition	14
plotBlocks	15
plotDeparcs	17
plotDeplogo	18
plotDepmatrix	21
replaceColors	22
revcom	23
subBoxes	23
subLines	24
suggestColors	25
summary.DLData	26
Index	27

Alphabet	<i>built alphabet</i>
----------	-----------------------

Description

builds an object of class Alphabet from the given set of symbols and colors

Usage

Alphabet(chars, cols)

Arguments

- | | |
|-------|------------------------------------|
| chars | set of symbols |
| cols | set of colors; one for each symbol |

Value

the Alphabet object

Author(s)

Martin Nettling

Examples

```
DNA <- Alphabet(c("A", "C", "G", "T"), c("green4", "blue", "orange", "red"))
```

alphabet.dna	<i>DNA alphabet</i>
--------------	---------------------

Description

DNA alphabet

Usage

alphabet.dna

Format

An object of class list of length 2.

alphabet.dna.gap	<i>DNA alphabet with gaps</i>
------------------	-------------------------------

Description

DNA alphabet with gaps

Usage

alphabet.dna.gap

Format

An object of class list of length 2.

alphabet.protein	<i>Amino acid alphabet</i>
------------------	----------------------------

Description

Amino acid alphabet

Usage

alphabet.protein

Format

An object of class list of length 2.

alphabet.protein.gap	<i>Amino acid alphabet with gaps</i>
----------------------	--------------------------------------

Description

Amino acid alphabet with gaps

Usage

alphabet.protein.gap

Format

An object of class list of length 2.

alphabet.rna	<i>RNA alphabet</i>
--------------	---------------------

Description

RNA alphabet

Usage

alphabet.rna

Format

An object of class list of length 2.

alphabet.rna.gap	<i>RNA alphabet with gaps</i>
------------------	-------------------------------

Description

RNA alphabet with gaps

Usage

alphabet.rna.gap

Format

An object of class list of length 2.

colorchart	<i>Plots a colorchart representation of a set of sequences</i>
------------	--

Description

This function is a low-level plotting function (using [image](#) with add=TRUE, internally).

Usage

```
colorchart(part, yoff, ic.scale = TRUE)
```

Arguments

part	the set of sequences as DLData object
yoff	the offset in y-direction within the current plot
ic.scale	ignored for colorcharts

Value

the vertical (y) offset after this plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[,1], weights = log1p(seqs[, 2]) )

# create high-level plot
plot(NULL, xlim = c(1, ncol(data$data) - 1), ylim = c(0, nrow(data$data)),
  ylab = nrow(data$data), axes = FALSE)
# and add colorchart and axis
colorchart(data, yoff = nrow(data$data))
axis(1)
```

deprects

Rectangles of averaged colors

Description

Plots a representation of a set of sequences by rectangles of (scaled) averaged color values of the symbols at each position

Usage

```
deprects(part, yoff, ic.scale = TRUE)
```

Arguments

part	the set of sequences as DLData object
yoff	the offset in y-direction within the current plot
ic.scale	if TRUE, alpha values of colors will be assigned based on "information content" of the distribution at each position

Details

This function is a low-level plotting function (using [rect](#), internally).

Value

the vertical (y) offset after this plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# create high-level plot
plot(NULL, xlim = c(1, ncol(data$data) - 1), ylim = c(0, nrow(data$data)),
  ylab = nrow(data$data), axes = FALSE)
# and add deprects and axis
deprects(data, yoff = nrow(data$data))
axis(1)
```

DLData	Create DLData object
--------	----------------------

Description

Creates a new DLData object from a set of input sequences.

Usage

```
DLData(  
  sequences,  
  weights = NULL,  
  symbols = alphabet.dna$alphabet,  
  colors = alphabet.dna$colors,  
  delim = "",  
  sortByWeights = !is.null(weights),  
  axis.labels = NULL  
)
```

Arguments

sequences	the input sequences, may be provided as i) character vector or ii) a data.frame with sequences organized in rows and one symbol per column
weights	weights associated with the sequences, numeric vector of the same length as sequences has sequences
symbols	the symbols (alphabet) over which the sequences are defined
colors	colors for each of the symbols, not necessarily unique
delim	delimiter between the symbols in the input sequences, ignored if sequences as a data.frame
sortByWeights	if TRUE, sequences will be ordered by their weight in decreasing order
axis.labels	the labels of the individual sequence positions; if NULL, indexes from 1 to total number of positions will be used

Details

Sequences may either be provided as a character vector or as a data.frame. All symbols occurring in these sequences need to be defined and assigned to colors, which are used for plotting later. Colors do not need to be unique, but symbols with identical colors may become indistinguishable in subsequent plots (which might even be desired, for instance, when visualizing protein properties instead of amino acids). Sequences may have an associated weight, which is used to order sequences, e.g., for creating chunks/blocks of sequences in subsequent plots (see chunks parameter of plotDeployo).

Value

the DLData object

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

[plotDeplogo](#)

Examples

```
# creating a DLData object using default (DNA) alphabet and colors
# from a character vector with two entries
data <- DLData(c("ACGT", "ATTA"))

# creating a DLData object using a custom, binary alphabet and custom colors
data2 <- DLData(c("A,B,B,A,B", "A,B,B,A,A", "A,B,A,A,B"),
  symbols = c("A", "B"), colors = c("red", "green"), delim = ",")

# creating a DLData object from a data frame
# (created from a character vector, in this case)
vec <- c("A,B,B,A,B", "A,B,B,A,A", "A,B,A,A,B")
df <- as.data.frame(t(sapply(vec, function(a){strsplit(a, ",")[[1]]})))
data.df <- DLData(df, symbols = c("A", "B"), colors = c("red", "green"))

# creating a DLData object from sequences and weights, read from a tabular file
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data3 <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )
```

filter.by.conservation

Filters columns (sequence positions) by conservation

Description

Filters columns based on the relative information content of each column which is the standard information content normalized to the interval [0,1], where 0 corresponds to uniform distribution and 1 to perfect conservation of one nucleotide or amino acid, respectively.

Usage

```
filter.by.conservation(relative.ic)
```

Arguments

`relative.ic` the maximum relative information content allowed to retain a position

Value

function that, given a [DLData](#) object, returns TRUE for every column that does not exceed the specified relative information content

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
fun <- filter.by.conservation(relative.ic = 0.9)
```

```
filter.by.dependencies
```

Filters columns (sequence positions) by dependency

Description

Filters columns based on the average or maximum mutual information of a column to all other columns. Mutual information is normalized to interval [0,1], where 0 corresponds to independence and 1 to perfect dependence.

Usage

```
filter.by.dependencies(mi.threshold, use.max = FALSE)
```

Arguments

mi.threshold	the minimum average or maximum mutual information required
use.max	if TRUE, the maximum and otherwise the average mutual information will be considered

Value

function that, given a [DLData](#) object, returns TRUE for every column that does exceed the specified average mutual information

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
fun <- filter.by.dependencies(mi.threshold = 0.3)
```

<code>filter.by.gaps</code>	<i>Filters columns (sequence positions) by gaps</i>
-----------------------------	---

Description

Filters columns (sequence positions) by gaps

Usage

```
filter.by.gaps(percent.gap)
```

Arguments

`percent.gap` the maximum fraction of gaps allowed to retain a column

Value

function that, given a [DLData](#) object, returns TRUE for every column that does not exceed the specified number of gaps

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
fun <- filter.by.gaps(percent.gap = 0.1)
```

<code>filterColumns</code>	<i>Filters data columns by some filter function</i>
----------------------------	---

Description

Filters the columns of the input data, i.e., positions of input sequences, by a filter function that, given a [DLData](#) object, returns a list containing i) as element `$selected` a vector with entries TRUE for every column that should be retained in the filtered data and ii) as element `$range` the range of values obtained for the filtering criterion.

Usage

```
filterColumns(data, filter.fun)
```

Arguments

`data` the data as [DLData](#) object
`filter.fun` the filter function

Value

a [DLData](#) object containing the filtered columns and the indexes of the remaining in its `axis.labels` field

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

[filter.by.gaps](#)

[filter.by.dependencies](#)

[filter.by.conservation](#)

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# create a filter function based on the percentage of gap symbols (at most 10%)
fun <- filter.by.gaps(percent.gap = 0.1)
data2 <- filterColumns(data, fun)
```

getDeps

Compute dependencies between positions

Description

Computes the dependencies (as measures by mutual information) between all positions (columns) of discrete data. Specifically, it returns for each pair of positions (i,j) the mutual information $I(X_i, X_j)$ multiplied by the number N of sequences (rows), which may also be used for testing the statistical significance of mutual information values, as for large N , $2*N*I(X_i, X_j)$ is approximately chi squared.

Usage

```
getDeps(data, ...)

## S3 method for class 'DLData'
getDeps(data, ...)

## S3 method for class 'data.frame'
getDeps(data, alphabet, ...)
```

Arguments

data	the data for computing mutual information. Either a DLData object or a data.frame; In the latter case, the symbols of the alphabet must be provided as a second parameter
...	the symbols of the alphabet as character vector, only if data is a data.frame
alphabet	only required when called on a data.frame

Value

a matrix of the mutual information values, where the diagonal is fixed to zero

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
data <- DLData(c("ACGT", "ATTA"))
deps <- getDeps(data)
```

getPwm

Position weight matrix from DLData object

Description

Determines the position weight matrix from a DLData object as relative frequency of symbols in each column of the data slot.

Usage

```
getPwm(part)

## S3 method for class 'DLData'
getPwm(part)
```

Arguments

part	the DLData object
------	-------------------

Value

the position weight matrix, where columns correspond to positions (columns of the DLData\$data slot) and rows to symbols

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
data <- DLData(c("ACGT", "ATTA"))
getPWM(data)
```

logo

Sequence logo

Description

Plots a representation of a set of sequences as a sequence logo

Usage

```
logo(part, yoff, ic.scale = TRUE)
```

Arguments

part	the set of sequences as DLData object
yoff	the offset in y-direction within the current plot
ic.scale	if TRUE, symbols are scaled by "information content" of the distribution at each position

Details

This function is a low-level plotting function (using [polygon](#), internally).

Value

the vertical (y) offset after this plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[,2]) )

# create high-level plot
plot(NULL, xlim = c(1, ncol(data$data) - 1), ylim = c(0, nrow(data$data)),
  ylab = nrow(data$data), axes = FALSE)
```

```
# and add sequence logo and axis
logo(data, yoff = nrow(data$data))
axis(1)
```

partition

Partitions data by most inter-dependent positions

Description

Partitions data by the nucleotides at the most inter-dependent positions as measures by pairwise mutual information. Partitioning is performed recursively on the resulting subsets until i) the number of sequences in a partition is less than `minElements`, ii) the average pairwise dependency between the current position and `numBestForSorting` other positions with the largest mutual information value drops below `threshold`, or iii) `maxNum` recursive splits have already been performed. If splitting results in smaller partitions than `minElements`, these are added to the smallest partition with more than `minElements` sequences.

Usage

```
partition(
  data,
  minElements = 10,
  threshold = 0.1,
  numBestForSorting = 3,
  maxNum = 6,
  sortByWeights = NULL,
  partition.by = NULL
)

## S3 method for class 'DLData'
partition(
  data,
  minElements = 10,
  threshold = 0.1,
  numBestForSorting = 3,
  maxNum = 6,
  sortByWeights = NULL,
  partition.by = NULL
)
```

Arguments

<code>data</code>	the data as DLData object
<code>minElements</code>	the minimum number of elements to perform a further split
<code>threshold</code>	the threshold on the average mutual information value
<code>numBestForSorting</code>	the number of dependencies to other positions considered

maxNum	the maximum number of recursive splits
sortByWeights	if TRUE, partitions are ordered by their average weight value, if false by frequency of symbols at the partitioning position otherwise. If NULL, the \$sortByWeights value of the DLData object is used
partition.by	specify fixed positions to partition by

Value

the partitions as list of [DLData](#) objects

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[,2]) )

# partition data using default parameters
partitions <- partition(data)

# partition data using a threshold of 0.3 on the mutual
# information value to the most dependent position,
# sorting the resulting partitions by weight
partitions2 <- partition(data = data, threshold = 0.3, numBestForSorting = 1, sortByWeights = TRUE)
```

plotBlocks

Plots blocks of data

Description

Plots the blocks of data in data by successive, vertically arranged sub-plots of the function provided as block.fun. If data is a single [DLData](#) object, one block is plotted. Further arguments are provided to block.fun.

Usage

```
plotBlocks(
  data,
  show.number = TRUE,
  block.fun = deprects,
  ic.scale = TRUE,
  add = FALSE,
  ...
)
```

```
## S3 method for class 'DLData'
plotBlocks(
  data,
  show.number = TRUE,
  block.fun = deprects,
  ic.scale = TRUE,
  add = FALSE,
  ...
)

## S3 method for class 'list'
plotBlocks(
  data,
  show.number = TRUE,
  block.fun = deprects,
  ic.scale = TRUE,
  add = FALSE,
  ...
)
```

Arguments

data	the data, a single DLData object or a list of DLData objects
show.number	if true, the number of sequences (in total) in data is displayed on the left side of the plot
block.fun	the function called for each of the blocks
ic.scale	if TRUE, output of block.fun may be scaled by "information content"
add	if TRUE, the plot is added to an existing plot
...	if add=FALSE forwarded to the internal call to plot

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

[deprects](#)
[logo](#)
[colorchart](#)

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )
```

```
# plot all data
plotBlocks(data)

# partition data
partitions <- partition(data, threshold = 0.3)
# and plot partitions
plotBlocks(partitions)

# or plot partitions as sequence logos
plotBlocks(partitions, block.fun = logo)
```

plotDeparcs

Plots a graph representation of dependency values

Description

Plots a representation of dependency values as arcs between the sequence positions. Internally, dependency values are computed using [getDeps](#) on the data object.

Usage

```
plotDeparcs(
  data,
  axis.at.bottom = TRUE,
  add.legend = TRUE,
  show.pvals = FALSE,
  axis.labels = NULL,
  threshold = 0.1
)
```

Arguments

data	the DLData object containing the data
axis.at.bottom	if TRUE, the x-axis is shown at the bottom (side=1) of the plot, and at the top (side=3) otherwise
add.legend	if TRUE a legend of the color scale is added to the plot
show.pvals	if TRUE, -log10 p-values (computed by pchisq) are shown instead of mutual information values
axis.labels	the labels of the x-axis
threshold	threshold in mutual information values, edges below this value are not shown; ignored in show.pvals=TRUE

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[,1], weights = log1p(seqs[, 2]) )

# plot using default parameters
plotDeparcs(data)

# plot with axis at top, without a legend (color scale), and using p-values
plotDeparcs(data, axis.at.bottom = FALSE, add.legend = FALSE, show.pvals = TRUE)
```

plotDeplogo

Plot a dependency logo

Description

Plots a dependency logo

Usage

```
plotDeplogo(
  data,
  dep.fun = plotDeparcs,
  block.fun = deprects,
  summary.fun = logo,
  weight.fun = NULL,
  chunks = NULL,
  chunk.height = 800,
  summary.height = 100,
  minPercent = 0.03,
  threshold = 0.1,
  numBestForSorting = 3,
  maxNum = 6,
  sortByWeights = NULL,
  dep.fun.legend = TRUE,
  show.dependency.pvals = FALSE,
  axis.labels = NULL,
  weight.ratio = 5,
  partition.by = NULL,
  ...
)

## S3 method for class 'DLData'
plotDeplogo(
  data,
  dep.fun = plotDeparcs,
```

```

    block.fun = deprects,
    summary.fun = logo,
    weight.fun = NULL,
    chunks = NULL,
    chunk.height = 800,
    summary.height = 100,
    minPercent = 0.03,
    threshold = 0.1,
    numBestForSorting = 3,
    maxNum = 6,
    sortByWeights = NULL,
    dep.fun.legend = TRUE,
    show.dependency.pvals = FALSE,
    axis.labels = NULL,
    weight.ratio = 5,
    partition.by = NULL,
    ...
)

```

Arguments

<code>data</code>	the data, currently implemented for DLData objects
<code>dep.fun</code>	the function for plotting the representation of dependency values (as computed by getDeps)
<code>block.fun</code>	the function for plotting a representation of the individual partitions of the data generated in dependency logos.
<code>summary.fun</code>	the function for plotting a representation of the summary plot for (one chunk of) the data
<code>weight.fun</code>	the function for plotting a representation of the weights values of the sequences within one partition
<code>chunks</code>	the size of chunks the data is split into. The sum of the chunk sizes must not be greater than the number of data points in data; The default value of NULL corresponds to one chunk containing all data points
<code>chunk.height</code>	the (relative) height of the parts of the plot representing each of the chunks, one height for each chunk
<code>summary.height</code>	the (relative) height of the block summaries in the plot
<code>minPercent</code>	the minimum percentage of the (sub) data set that may constitute its own partition in the dependency logo
<code>threshold</code>	the threshold on the dependency value for further splits
<code>numBestForSorting</code>	the number of dependencies between position <i>i</i> and all other positions when computing the dependency value of position <i>i</i>
<code>maxNum</code>	the maximum number of splits allowed
<code>sortByWeights</code>	are partitions sorted by their average weight (descending)

<code>dep.fun.legend</code>	if TRUE, a legend of the color scale used for plotting the dependency values in <code>dep.fun</code> is added to the plot
<code>show.dependency.pvals</code>	is TRUE, p-values are used for plotting dependency values in <code>dep.fun</code> instead of mutual information values
<code>axis.labels</code>	labels for the x-axis, vector of the same length as the individual sequences
<code>weight.ratio</code>	the factor by which the plotting width for the main plot is larger than for <code>weight.fun</code>
<code>partition.by</code>	specify fixed positions to partition by
<code>...</code>	forwarded to the high-level plot that contains the blocks plotted by <code>block.fun</code>

Details

The function `dep.fun` provided for plotting the representation of dependencies is currently implemented in [plotDeparcs](#) and [plotDepmatrix](#). Custom implementations must have the same signature as these functions and create a single plot without using [layout](#) (or similar).

The functions `block.fun` and `summary.fun` provided for plotting the representation of individual partitions of the data generated in dependency logos are currently implemented in [deprects](#), [colorchart](#), and [logo](#). Custom implementations must have the same signature as these functions and create a single plot without using [layout](#) (or similar).

The function `weight.fun` for plotting a representation of the weights values of the sequences within one partition is currently implemented in [subLines](#) and [subBoxes](#). Custom implementations must have the same signature as these functions and create a single plot without using [layout](#) (or similar).

Value

a list of [DLData](#) objects with the partitions created for the dependency logo

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# plot default dependency logo
plotDeplogo(data)

# refine threshold for clearer picture
plotDeplogo(data, threshold = 0.3)

# customize different parts of the plot
plotDeplogo(data, threshold = 0.3, dep.fun = plotDepmatrix, block.fun = colorchart)

# add plots of the weights
```

```
plotDeplogo(data, weight.fun = subBoxes)
```

plotDepmatrix

Plots a matrix representation of dependency values

Description

Plots a representation of dependency values as a triangular matrix rotated by 45 degrees. Internally, dependency values are computed using [getDeps](#) on the data object.

Usage

```
plotDepmatrix(
  data,
  axis.at.bottom = TRUE,
  add.legend = TRUE,
  show.pvals = FALSE,
  axis.labels = NULL,
  threshold = 0.1
)
```

Arguments

data	the DLData object containing the data
axis.at.bottom	if TRUE, the x-axis is shown at the bottom (side=1) of the plot, and at the top (side=3) otherwise
add.legend	if TRUE a legend of the color scale is added to the plot
show.pvals	if TRUE, -log10 p-values (computed by pchisq) are shown instead of mutual information values
axis.labels	the labels of the x-axis
threshold	ignored

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# plot using default parameters
plotDepmatrix(data)

# plot with axis at top, without a legend (color scale), and using p-values
plotDepmatrix(data, axis.at.bottom = FALSE, add.legend = FALSE, show.pvals = TRUE)
```

replaceColors	<i>Replaces colors in DLData object</i>
---------------	---

Description

Replaces colors in [DLData](#) object

Usage

```
replaceColors(data, colors)

## S3 method for class 'DLData'
replaceColors(data, colors)
```

Arguments

data	the data
colors	the new colors

Value

the modified [DLData](#) object

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

[replaceColors](#)

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

replaceColors(data, c("red", "green", "blue", "yellow"))
```

revcom	<i>Reverse complement</i>
--------	---------------------------

Description

Determine the reverse complementary DLData object. Only works for DNA or RNA. Data may include gap symbols.

Usage

```
revcom(data)

## S3 method for class 'DLData'
revcom(data)
```

Arguments

data the data

Value

the reverse complement

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
data <- DLData(c("ACGT", "ATTA"))
revcom(data)
```

subBoxes	<i>Plots weights as boxplots</i>
----------	----------------------------------

Description

Plots a representation of the weights of a list of [DLData](#) objects. Each entry of the list is shown as an independent boxplot.

Usage

```
subBoxes(sub.parts, range, axis.above = TRUE, axis.below = TRUE)
```

Arguments

sub.parts	a list of DLData objects
range	the range of values shown in the plot (i.e., the xlim value of the call to plot)
axis.above	if TRUE, an axis at the top of the plot (side=3) is shown
axis.below	if TRUE, an axis at the bottom of the plot (side=1) is shown

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "nrsf.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# create dependency logo with plotted weights
plotDeplogo(data, threshold = 0.03, weight.fun = subBoxes)
```

subLines	<i>Plots weights as lines</i>
----------	-------------------------------

Description

Plots a representation of the weights of a list of [DLData](#) objects. Each entry of the list is shown as an independent line with the median value shown as a red vertical line. Plots of list entries are separated by horizontal grey lines.

Usage

```
subLines(sub.parts, range, axis.above = TRUE, axis.below = TRUE)
```

Arguments

sub.parts	a list of DLData objects
range	the range of values shown in the plot (i.e., the xlim value of the call to plot)
axis.above	if TRUE, an axis at the top of the plot (side=3) is shown
axis.below	if TRUE, an axis at the bottom of the plot (side=1) is shown

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "nrsf.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )

# create dependency logo with plotted weights
plotDeplogo(data, threshold = 0.03, weight.fun = subLines)
```

suggestColors	<i>Suggests colors for symbols</i>
---------------	------------------------------------

Description

Suggests colors for the symbols in data based on the co-occurrence of symbols at common positions, weighted by the dependency values at those positions. The idea is to assign similar colors only to symbols that either mostly occur at different positions or that are present at positions with low inter-dependencies to other positions.

Usage

```
suggestColors(data)

## S3 method for class 'DLData'
suggestColors(data)
```

Arguments

data the data

Value

the colors

Author(s)

Jan Grau <grau@informatik.uni-halle.de>

See Also

[replaceColors](#)

Examples

```
# read data and create DLData object
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1] ,weights = log1p(seqs[, 2]) )

suggestColors(data)
```

summary.DLData*Summarizing DLData objects*

Description

summary method for class "DLData". The summary includes the number of sequences, the consensus sequence and the number of sequences in object that match the consensus.

Usage

```
## S3 method for class 'DLData'
summary(object, delete.gaps = FALSE, ...)
```

Arguments

object	an object of class "DLData"
delete.gaps	if gaps should be removed from the consensus
...	further arguments passed to or from other methods

Value

a list with elements members containing the number of sequences, consensus containing the consensus sequences, and equal.consensus containing the number of sequences in object that are identical to consensus

Author(s)

Jens Keilwagen, Jan Grau <grau@informatik.uni-halle.de>

Examples

```
seqs <- read.table(system.file("extdata", "cjun.txt", package = "DepLogo"),
  stringsAsFactors = FALSE)
data <- DLData(sequences = seqs[, 1], weights = log1p(seqs[, 2]) )
summary(data)
```

Index

* datasets

- alphabet.dna, [3](#)
- alphabet.dna.gap, [3](#)
- alphabet.protein, [3](#)
- alphabet.protein.gap, [4](#)
- alphabet.rna, [4](#)
- alphabet.rna.gap, [4](#)

Alphabet, [2](#)

- alphabet.dna, [3](#)
- alphabet.dna.gap, [3](#)
- alphabet.protein, [3](#)
- alphabet.protein.gap, [4](#)
- alphabet.rna, [4](#)
- alphabet.rna.gap, [4](#)

colorchart, [5](#), [16](#), [20](#)

deprects, [6](#), [16](#), [20](#)

DLData, [5](#), [6](#), [7](#), [8–11](#), [13–17](#), [19–24](#)

filter.by.conservation, [8](#), [11](#)

filter.by.dependencies, [9](#), [11](#)

filter.by.gaps, [10](#), [11](#)

filterColumns, [10](#)

getDeps, [11](#), [17](#), [19](#), [21](#)

getPWM, [12](#)

image, [5](#)

layout, [20](#)

logo, [13](#), [16](#), [20](#)

partition, [14](#)

pchisq, [17](#), [21](#)

plot, [16](#), [24](#)

plotBlocks, [15](#)

plotDeparcs, [17](#), [20](#)

plotDeplogo, [8](#), [18](#)

plotDepmatrix, [20](#), [21](#)

polygon, [13](#)

rect, [6](#)

replaceColors, [22](#), [22](#), [25](#)

revcom, [23](#)

subBoxes, [20](#), [23](#)

subLines, [20](#), [24](#)

suggestColors, [25](#)

summary.DLData, [26](#)